



Operator Overloading



C++ Object Oriented Programming
Pei-yih Ting
NTOU CS



Contents

- ❖ Basics
- ❖ Consider all usages of the overloaded operator
- ❖ Complex number example
- ❖ Do not change semantics
- ❖ Overload related sets of operators
- ❖ Time example
- ❖ Prefix ++ and postfix ++
- ❖ operator[]
- ❖ Assignment operator: operator=
- ❖ Function call operator: operator()
- ❖ Smart pointers
- ❖ Memory allocation operators: operator new/delete
- ❖ Type conversion operators
- ❖ Unary operator+

Basic Overloading

- ❖ Operator overloading in ANSI C

```
int x, y, z;
double q, r, t;
z = x + y;
q = r + t;
```

The same operator can do different things.

- ❖ Overloading in C++

```
Array();
Array(int arraySize);
```

Overloaded constructors

```
void quit() {
    cout << "So you want to save before quitting?\n";
}
void quit(char *customMessage) {
    cout << customMessage << endl;
}
```

The same function name can do different jobs.

Operator Overloading

- ❖ There are two possibilities for the following

```
MyClass obj1, obj2;
obj1 + obj2;
```

Compiler would translate the above into one of the following function call if one of them is defined:

- * First: calling member function
MyClass MyClass::operator+(MyClass rhs)
i.e. obj1.operator+(obj2)
- * Second: calling global function
MyClass operator+(MyClass lhs, MyClass rhs)
i.e. operator+(obj1, obj2)

If both of them are defined, the global one will be invoked.

Operator Overloading

- Consider the following MenuItem class which describe the item on a restaurant menu

```
class MenuItem {
public:
    MenuItem(int itemPrice, char *itemName);
    MenuItem(const MenuItem &src);
    ~MenuItem();
    void display() const;
private:
    int m_price;
    char *m_name;
};
```

- We would like to do the following

```
void main() {
    MenuItem item1(250, "Chicken Florentine");
    MenuItem item2(120, "Tiramisu");
    cout << "You ordered the following items:";
    item1.display(); item2.display();
    cout << "The total is $" << item1 + item2 << ".\n";
}
```

5

First Solution with Overloading

- Add a member function which overloads operator+()

```
class MenuItem
{
public:
    MenuItem(int itemPrice, char *itemName);
    MenuItem(const MenuItem &src);
    ~MenuItem();
    void display() const;
    int operator+(MenuItem &secondItem) const;
private:
    int m_price;
    char *m_name;
};
```

or MenuItem secondItem

- The function is defined as follows

```
int MenuItem::operator+(MenuItem &secondItem) const
{
    return m_price + secondItem.m_price;
}
```

Left operand of + Right operand of +

6

Behavior of Overloaded Operator

- Add a third menu item

```
MenuItem item1(250, "Chicken Florentine");
MenuItem item2(120, "Tiramisu");
MenuItem item3(50, "Mineral Water");
int total;
```

```
total = item1 + item2 + item3;
```

Why?

error C2677: binary '+' : no global operator defined which takes type 'class MenuItem' (or there is no acceptable conversion)

- * item1 + item2 returns an int
- * you then have int + item3

The overloaded member function can only be called by an instance of the class.

- Solution: make the overloaded function toplevel

```
int operator+(int currentTotal, MenuItem &secondItem)
{
    return currentTotal + secondItem.m_price;
}
```

make this function a friend of MenuItem

could be reference or value, but not both

7

Behavior of Overloaded Operator

- The following statement still fail

```
item1 + (item2 + item3)
```

error C2678: binary '+' : no operator defined which takes a left-hand operand of type 'class MenuItem' (or there is no acceptable conversion)

Why?

- * This is equivalent to item1 + int

- Solution: add another overloaded operator function

```
int MenuItem::operator+(int currentTotal) {
    return currentTotal + m_price;
}
```

Why does this function not have to be toplevel (i.e. global)?

- Conclusion

When you overload an operator, you are responsible for the correct behavior of the operator in all possible circumstances.

8

Alternative Solution

- Use conversion operator and global operator+(MenuItem &, MenuItem &)

```
class MenuItem {
    friend int operator+(MenuItem &firstItem, MenuItem &secondItem);
public:
    MenuItem(int itemPrice, char *itemName);
    MenuItem(int price);
    MenuItem(const MenuItem &src);
    ~MenuItem();
    void display() const;
private:
    int m_price;
    char *m_name;
};
```
- The conversion constructor

```
MenuItem::MenuItem(int price): m_price(price), m_name(0) {
}
```
- Overload the operator at the toplevel with two MenuItem objects

```
int operator+(MenuItem &firstItem, MenuItem &secondItem) {
    return firstItem.m_price + secondItem.m_price;
}
```

9

Complex Number Example

- Complex class represents a complex number (real, imaginary), define two mathematic operations

```
Complex Complex::add(Complex &secondNumber) const {
    Complex tmp(m_real+secondNumber.m_real,
                m_imaginary+secondNumber.m_imaginary);
    return tmp;
}
Complex Complex::multiply(Complex &secondNumber) const {
    Complex tmp(m_real*secondNumber.m_real-
                m_imaginary*secondNumber.m_imaginary,
                m_real*secondNumber.m_imaginary+
                m_imaginary*secondNumber.m_real);
    return tmp;
}
```
- main()

```
Complex c(0.1, 0), z(0, 0);
for (int i=1; i<MaxIterations; i++) {
    z = c.add(z.multiply(z));
    if (fabs(z.getRealPart())>2.0 || fabs(z.getImaginaryPart())>2.0) break;
}
```

10

Complex Number (cont'd)

- Let us overload + and *

```
Complex Complex::operator+(Complex &secondNumber) const {
    Complex tmp(m_real+secondNumber.m_real,
                m_imaginary+secondNumber.m_imaginary);
    return tmp;
}
Complex Complex::operator*(Complex &secondNumber) const {
    Complex tmp(m_real*secondNumber.m_real-
                m_imaginary*secondNumber.m_imaginary,
                m_real*secondNumber.m_imaginary+
                m_imaginary*secondNumber.m_real);
    return tmp;
}
```
- main()

```
Complex c(0.1, 0), z(0, 0);
for (int i=1; i<MaxIterations; i++) {
    z = c + z * z;
    if (fabs(z.getRealPart())>2.0 || fabs(z.getImaginaryPart())>2.0) break;
}
```
- Related operators +=, *=

11

Dubious Operator Overloading

- Here are some actual examples from a textbook
Can you guess what these operators mean?

```
Stack s;
...
s+5;
x = s--;
```

They stand for the following

```
s.push(5);
x = s.pop();
```
- Overloading obscure operators can be dangerous
Redefine ^ (bitwise XOR) to mean "power"
It won't work as expected, ex.
 $x^2 + 1$ // if x is 5, you want 26 but you will get 125
Reason: ^ has less precedence than +
- Illegal overloading

error C2803: 'operator +' must have at least one formal parameter of class type

```
int operator+(int number1, int number2) {
    return number1-number2;
}
```

12

Overload All Related Operators

✧ If you provide a + operator, you should also provide related operators such as += and ++

✧ Let us define a Time class that allows addition

```
class Time {
public:
    Time();
    Time(int hours, int minutes, int seconds);
    void display();
    Time operator+(Time secondTime);
private:
    int m_hours;
    int m_minutes;
    int m_seconds;
    void normalize();
};
Time::Time(): m_seconds(0), m_minutes(0), m_hours(0) {
}
Time::Time(int hours, int minutes, int seconds)
: m_hours(hours), m_minutes(minutes), m_seconds(seconds) {
    normalize();
}
```

Overload + and *

✧ operator+

```
Time Time::operator+(Time secondTime){
    int hours, minutes, seconds;
    hours = m_hours + secondTime.m_hours;
    minutes = m_minutes + secondTime.m_minutes;
    seconds = m_seconds + secondTime.m_seconds;
    return Time(hours, minutes, seconds);
}
```

Note; we do not call normalize() in this case

```
Time time1(20, 15, 0);
Time time2(3, 45, 10);

Time time3 = time1 + time2;
time3.display();
cout << endl;

time2 *= 3;
time2.display();
cout << endl;
```

✧ operator*=
This operator does not return anything and has side effects.

```
void Time::operator*=(int num) {
    m_hours *= num;
    m_minutes *= num;
    m_seconds *= num;
    normalize();
}
```

operator++

✧ ++ and -- come in postfix and prefix format

```
int x, y;
x = 5;
y = x++;
cout << "x is " << x << " and y is " << y << "\n";
```

Output
x is 6 and y is 5

```
x = 5;
y = ++x;
cout << "x is " << x << " and y is " << y << "\n";
```

Output
x is 6 and y is 6

✧ How does C++ know which ++ operator you want to override?

★ Postfix syntax

```
Time Time::operator++(int) // int argument is ignored
```

★ Prefix syntax

```
Time time::operator++()
```

operator++ (cont'd)

✧ Postfix operator

```
Time Time::operator++(int) {
    Time tmp = *this;
    m_seconds++; normalize();
    return tmp;
}
```

✧ Usage

```
Time firstTime(1, 1, 3), secondTime;
secondTime = firstTime++;
firstTime.display(); secondTime.display();
```

Output
01:01:04
01:01:03

✧ Prefix operator

```
Time Time::operator++() {
    m_seconds++; normalize();
    return *this;
}
```

✧ Usage

```
Time firstTime(1, 1, 3), secondTime;
secondTime = ++firstTime;
firstTime.display(); secondTime.display();
```

Output
01:01:04
01:01:04

operator[]

- ◇ An array class which includes bounds checking

```
class Array {
public:
    Array();
    Array(int arraySize);
    ~Array();
    void insert(int slot, int element);
    int get(int slot) const;
private:
    int m_arraySize;
    int *m_array;
};

void Array::insert(int slot, int element) {
    if (slot < m_arraySize && slot >= 0)
        m_array[slot] = element;
    else
        cout << "Subscript out of range\n";
}

int Array::get(int slot) const {
    if (slot < m_arraySize && slot >= 0)
        return m_array[slot];
    cout << "Subscript out of range\n";
    return 0;
}
```

```
Array data(5);
for (int i=0; i<5; i++)
    data.insert(i, i*2);
cout << data.get(3);
```

We would like the same syntax as a "normal" array.

```
Array data(5);
for (int i=0; i<5; i++)
    data[i] = i*2;
cout << data[3];
```

17

operator[] (cont'd)

```
class Array {
public:
    Array();
    Array(int arraySize);
    ~Array();
    int &operator[](int slot);
private:
    int m_arraySize;
    int *m_array;
};

int &Array::operator[](int slot) {
    if (slot < m_arraySize && slot >= 0)
        return m_array[slot];
    cout << "Subscript out of range\n";
    return m_array[0];
}
```

Work as lvalue

18

The Account Example

```
class Account
{
public:
    Account(const char *name, const char *phone, const char *address);
    ~Account();
    ....
private:
    char *m_name;
    char *m_phone;
    char *m_address;
};

Account::Account(const char *name, const char *phone, const char *address)
{
    m_name = new char[strlen(name)+1]; strcpy(m_name, name);
    m_phone = new char[strlen(phone)+1]; strcpy(m_phone, phone);
    m_address = new char[strlen(address)+1]; strcpy(m_address, address);
}

Account::~Account()
{
    delete[] m_name; delete[] m_phone; delete[] m_address;
}
```

19

Assignment Operator

- ◇ Where is the assignment operator invoked?
Account customer1("abc", "1234", "ABC street");
Account customer2, customer3; // assume default ctor defined
customer2 = customer1;
customer2.operator=(customer1);
customer3 = customer2 = customer1;
- ◇ Note: Account customer2 = customer1;
does not invoke the assignment operator

- ◇ What is its prototypes?

```
Account &operator=(Account &rhs);
```



No extra copy ctor invoked

Designed for continuously assignment

```
customer3.operator=(customer2.operator=(customer1));
```

20

Assignment Operator

✧ Again, if the class being designed allocates its own resources. It is quite often to see the dtor, copy ctor, and the assignment operator occur together.

✧ There are seven important things to do in an assignment operator

```
Account &Account operator=(Account &rhs)
{
    ① if (&rhs == this) return *this; ← Detecting self assignments
    ② delete[] m_name; delete[] m_phone; delete[] m_address;
    ③ { m_name = new char[strlen(rhs.m_name)+1];
      m_phone = new char[strlen(rhs.m_phone)+1];
      m_address = new char[strlen(rhs.m_address)+1];
    }
    ④ { strcpy(m_name, rhs.m_name);
      strcpy(m_phone, rhs.m_phone);
      strcpy(m_address, rhs.m_address);
    }
    ⑤ // invoke the base class assignment operator
    ⑥ // invoke the component object assignment operator
    ⑦ return *this;
}
```

21

Related Operators of Assignment

✧ If you overload assignment, you might like to overload equality

```
bool Account::operator==(const Account &rhs) const {
    if ((strcmp(m_name, rhs.m_name)==0) &&
        (strcmp(m_phone, rhs.m_phone)==0) &&
        (strcmp(m_address, rhs.m_address)==0))
        return true;
    else
        return false;
}
```

✧ Usage

```
Account customer1("abc", "1234", "ABC street"), customer2;
customer2 = customer1;
...
if (customer2 == customer1) ...
```

✧ Other operators

```
* bool operator!=(const Account &rhs) const;
* bool operator<(const Account &rhs) const;
* bool operator<=(const Account &rhs) const;
* bool operator>(const Account &rhs) const;
* bool operator>=(const Account &rhs) const;
```

22

Function Call operator()

✧ Overload operator() to make an object that stands for a function behave like a function

```
class Polynomial {
public:
    Polynomial(double secondOrder, double firstOrder, double constant);
    double operator()(double x);
private:
    double m_coefficients[3];
};
Polynomial::Polynomial(double secondOrder, double firstOrder, double constant) {
    m_coefficients[2] = secondOrder;
    m_coefficients[1] = firstOrder;
    m_coefficients[0] = constant;
}
double Polynomial::operator()(double x) {
    return m_coefficients[2]*x*x + m_coefficients[1]*x + m_coefficients[0];
}
void main() {
    Polynomial f(2, 3, 4);
    int x = 2;
    cout << f(x);
}
```

Output
18

23

Other Uses of operator()

✧ operator() is the only operator that can take any number of arguments

✧ Imagine you had a matrix class (two-dimensional array): You would like to avoid accessor and mutator functions. One idea is to overload the operator[], the subscript operator.

✧ This is illegal

```
int &operator[][](int x);
```

✧ The closest equivalent to array subscripting is to overload operator() with two arguments

```
int &Matrix::operator()(int x, int y) {
    if (x>=0 && x<m_dim1 && y>=0 && y < m_dim2)
        return m_matrix[x][y];
    cout << "out of bounds!\n";
    return m_matrix[0][0];
}
```

✧ Usage

```
Matrix matrix(5,10);
matrix(2,3) = 10; cout << matrix(2,3);
```

24

Smart Pointers

- ◇ When you overload \rightarrow , you get a *smart pointer*
The primary purpose of a smart pointer is to link a member function of a subobject to the main object

- ◇ Example:

```
class Person {
public:
    Person(char *name, int age)
    int getAge();
    Name *operator->();
private:
    Name *m_nameObject; // must be a pointer
    int m_age;
};
class Name {
public:
    Name(char *name);
    ~Name();
    const char *getName();
private:
    char *m_name;
};
```

- ★ The goal is to link Name::getName() to an instance of type Person

25

Smart Pointers (cont'd)

- ◇ The overloaded function

```
Name *Person::operator->() {
    return m_nameObject;
}
```

- ◇ Using the smart pointer

```
void main() {
    Person person("Harvey", 12);
    cout << person->getName();
}
```

Note that *person* is not a pointer.

- ◇ Evaluating rules of a smart pointer:

If the object is a pointer, \rightarrow operator is evaluated as it normally is.
If it is a static object with an overloaded \rightarrow operator, the object is replaced by the output of the function

```
person->getName()  —————>  m_nameObject->getName();
```

The process continues until evaluation occurs normally (i.e. the lhs of \rightarrow operator is a pointer).

26

operator new / operator delete

- ◇ You can have your own new and delete for a particular object

```
class Random {
public:
    Random(int data);
    int getData();
    void *operator new(size_t objectSize);
    void operator delete(void *object);
private:
    int m_data;
};
void *Random::operator new(size_t objectSize) {
    cout << "new\n";
    return malloc(objectSize);
}
void Random::operator delete(void *object) {
    cout << "delete\n";
    free(object);
}
```

- ◇ Usage:

```
void main() {
    Random *ptr = new Random;
    delete ptr;
}
```

27

operator new[] / operator delete[]

```
class Random {
public:
    Random(int data);
    int getData();
    void *operator new[](size_t objectSize);
    void operator delete[](void *object);
private:
    int m_data;
};
void *Random::operator new[](size_t objectSize) {
    cout << "new[] objectSize=" << objectSize << "\n";
    return malloc(objectSize);
}
void Random::operator delete[](void *object) {
    cout << "delete[]\n";
    free(object);
}
```

- ◇ Usage:

```
void main() {
    Random *ptr = new Random[5];
    delete[] ptr;
}
```

28

operator new / operator delete

- ◇ Why should one override new, new[], delete, delete[]?
 - ★ One can allocate/deallocate memory from an internal memory pool instead of standard malloc/free
- ◇ Can you see why new[]/delete or new/delete[] would fail?
 - ★ In delete[] operator, the default implementation should try to invoke destructors for all objects. If that block of memory was allocated with new.... Error occurs
 - ★ In delete operator, the default implementation only invoke destructor once. If that block of memory was allocated with new[] ... Many objects will not be suitably destructed

29

Type Conversion

- ◇ Consider a simple string class

```
class String {
public:
    String();
    String(char *inputData);
    String(const String &src);
    ~String();
    const char *getString() const;
private:
    char *m_string;
};
```
- ◇ This class allows conversions from ANSI C char arrays to the object of this class through the type conversion constructor

```
void main() {
    String string1("hello");
    String string2 = "bye"; // type conversion ctor then copy ctor
}
```
- ◇ What about conversions in the other direction, from String class to ANSI C char array?

30

Type Conversion (cont'd)

- ◇ Type conversion operator (type coercion)

```
class String {
public:
    ....
    String(const String &src);
    operator const char *() const;
    ....
private:
    char *m_string;
};
```
- ◇ The definition

```
String::operator const char *() const {
    return m_string;
}
```

 - ★ The function has no return type, in spite of the fact that it does return something!!!
- ◇ Usage

```
void main() {
    String strObj("hello");
    cout << strlen(strObj) << "\n";
    cout << strObj << " " << (const char *)strObj << "\n";
}
```

```
Output
5
00341E60 Hello
```

31

Overload Unary +

- ◇ Binary syntax: object1 - object2

```
Complex Complex::operator-(Complex &secondNumber) const {
    Complex tmp(m_real-secondNumber.m_real,
                m_imaginary-secondNumber.m_imaginary);
    return tmp;
}
```
- ◇ Unary syntax: -object

```
Complex Complex::operator-() const {
    return Complex(-m_real, -m_imaginary);
}
```

32

Miscellaneous

◇ Can you overload every operator?

* No.

* There are some operator that cannot be overloaded

·

.*

::

?:

sizeof

◇ Can you create new operators?

* No. For example, you cannot do this: `y:=x;`