

Contents

- ❖ Classes that need other classes
- ❖ Friend member functions in C++
- ❖ Do we really need friends in C++?
- ❖ Granting friendship to another class
- ❖ Granting friendship to another function
- ❖ Company database example
- ❖ Linked list example
- ❖ Containers and iterators

2

Friends



C++ Object Oriented Programming
Pei-yih Ting
NTOU CS

• • • • • • • • 1

Classes That Need Other Classes

```
class Data
{
public:
    Data(int x):m_x(x) {}
    int getData() const;
private:
    int m_x;
};

int Data::getData() const
{
    return m_x;
}

void main()
{
    Data data(10);
    General object;
    object.printX(data);
}
```

```
class General
{
public:
    void printX(Data inputObject);
};

void General::printX(Data inputObject)
{
    cout << inputObject.getData() << "\n";
}
```

Output
10

3

Friend Class

```
class Data
{
friend class General; // can be put anywhere in the class
public:
    Data(int x):m_x(x) {}
private:
    int m_x;
};

class General
{
public:
    void printX(Data inputObject);
};

void main()
{
    Data data(10);
    General object;
    object.printX(data);
}
```

❖ Note: friendship is granted, not taken

4

Friend Member Function

- “Friendship” can be restricted to a specific function
- Suppose we have another function printIntro() in General but we don’t want to grant it the access to Data::m_x

```
class General {  
public:  
    void printX(Data inputObject);  
    void printIntro();  
};  
void General::printIntro() {  
    cout << "Welcome to the General class.";  
}  
  
class Data {  
friend void General::printX(Data inputObject);  
public:  
    Data(int x):m_x(x) {}  
private:  
    int m_x;  
};
```

5

Implication of Friends

- Granting friend classes in C++ essentially **breaks the encapsulation** of one class. Basically, the class and its friend classes should be considered as a whole body. When you try to modify any implementation of the class, you need to think of all possible usages in its friend classes and friend functions.
- A class is a natural module in C++. However, in some design patterns, several separate class interfaces could capture more precisely the **physical operating mechanisms**. These classes operate on many common data, have strong coupling, and need to be considered as a whole module.
- If you are not considering such kind of physical operating models, **do NOT** grant a friend class or a friend function just because it is convenient to write codes or to save the time in designing suitable interfaces and abstractions.

6

Example: Company Database

- Assume we have a company database program in which a “manager” class needs to access an employee class

```
class Manager {  
public:  
    void doJob(Employee *worker);  
private:  
    void fireEmployee(Employee *worker);  
};
```

- The Employee class makes the name of the employee public but not the salary. Since the manager class needs information of both, the Employee class will grant partial friendship to Manager::doJob()

```
class Employee {  
friend void Manager::doJob(Employee *worker);  
public:  
    Employee(const char *name, long salary);  
    ~Employee();  
    char *getName() const;  
private:  
    long getSalary() const;  
    char *m_name;  
    long m_salary;  
};
```

7

Example (cont’d)

```
void Manager::doJob(Employee *worker)  
{  
    if(worker->getSalary()<100000 && worker->getSalary()>40000)  
        fireEmployee(worker);  
}
```

getSalary() is a private member function of Employee.

```
void Manager::fireEmployee(Employee *worker)  
{  
    cout << "Employee " << worker->getName() << " has been terminated.\n";  
    delete worker;  
}
```

getName() is a public member function, so fireEmployee() need not be a friend

```
void main()  
{  
    Employee *worker;  
    Manager *boss;  
    worker = new Employee("Wally", 45000);  
    boss = new Manager;  
    boss->doJob(worker);  
}
```

Output
Employee Wally has been terminated.

8

Example: Link List

- Suppose we want to implement a linked list class for storing integers. We can do this by means of two classes, one for the data, the other for the linked list itself.

```
class Data {  
    friend class LinkedList;  
private:  
    Data(int value);  
    int m_value;  
    Data *m_next;  
};  
  
class LinkedList {  
public:  
    LinkedList();  
    ~LinkedList();  
    void append(int value);  
    void display();  
private:  
    Data *m_tail, *m_head;  
};
```

No public interface is defined in this class

9

Link List (Cont'd)

- Member functions

```
Data::Data(int value): m_value(value), m_next(0)  
{  
}  
  
LinkedList::LinkedList(): m_head(0), m_tail(0)  
{  
}  
  
void LinkedList::append(int value)  
{  
    Data *temp = new Data(value);  
    if (m_head == 0) {  
        m_head = temp;  
        m_tail = temp;  
    }  
    else {  
        m_tail->m_next = temp;  
        m_tail = temp;  
    }  
}
```

When do you need
a destructor for Data?

10

Link List (Cont'd)

- Member functions

```
LinkedList::~LinkedList()  
{  
    Data *current, *next;  
    current = m_head;  
    while (current != 0)  
    {  
        next = current->m_next;  
        delete current;  
        current = next;  
    }  
}
```

```
void LinkedList::display()  
{  
    Data *temp;  
    for (temp=m_head; temp!=0;  
         temp=temp->m_next)  
        cout << temp->m_value << " ";  
}
```

- Main

```
void main()  
{  
    LinkedList myLinkedList;  
    myLinkedList.append(1);  
    myLinkedList.append(2);  
    myLinkedList.display();  
}
```

Output
1 2

11

Containers and Iterators

- A container class is a class designed to hold a collection of objects. Typical containers are arrays, linked lists, trees, stacks, and queues.
- Using polymorphic pointers, a container can hold heterogeneous objects.
- An iterator data member allows the client to step through the container.

```
Array::Array(int arraySize)  
: m_arraySize(arraySize), m_iterator(-1){  
    m_array = new int[arraySize];  
}  
  
Array(int arraySize);  
~Array();  
void insertElement(int slot, int element);  
void reset(); // Iterator function  
int next(); // Iterator function  
  
private:  
    int m_arraySize;  
    int *m_array;  
    int m_iterator;  
};
```

12

Containers and Iterators (cont'd)

```

int Array::next() {
    m_iterator++;
    if (m_iterator < m_arraySize)
        return m_array[m_iterator];
    cout << "There are no additional elements in the array.\n";
    return 0;
}

void main() {
    Array array(2);
    array.insertElement(0, 6);
    array.insertElement(1, 10);
    cout << array.next() << "\n";
    cout << array.next() << "\n";
    cout << array.next() << "\n";
    array.reset();
    cout << array.next() << "\n"; cout << array.next() << "\n";
}

```

Output

```

6
10
There are no additional elements in the array
6
10

```

13

Iterators (Cont'd)

```

int *Iterator::next(Array &array) {
    m_iterator++;
    if (m_iterator < array.m_arraySize)
        return &array.m_array[m_iterator];
    return 0;
}

void main() {
    int result = 0;
    Array array(2);
    Iterator iter1, iter2;
    int *i, *j;

    array.insertElement(0, 2);
    array.insertElement(1, 3);
    for(i= iter1.next(array); i!=0; i=iter1.next(array), iter2.reset())
        for(j=iter2.next(array); j!=0; j=iter2.next(array))
            result += pow(j, i);
    cout << "Result = " << result << endl;
}

```

```

Iterator::Iterator(): m_iterator(-1) {
}

void Iterator::reset() {
    m_iterator = -1;
}

```

$$2^2 + 3^2 + 2^3 + 3^3$$

Output
Result = 48

15

Containers and Iterators with Friends

- ❖ Better implementation with a separate Iterator class declared using a friend function. Why? will show in the next slide.

```

class Array;
class Iterator {
public:
    Iterator();
    void reset();
    int *next(Array &array);
private:
    int m_iterator;
};

```

```

class Array {
    friend int *Iterator::next(Array &array);
public:
    Array(int arraySize);
    ~Array();
    void insertElement(int slot, int element);
private:
    int m_arraySize;
    int *m_array;
};

```

14

Containers and Iterators with Friends

- ❖ Better implementation with a separate Iterator class declared using a friend function. Each iterator instance is associated with a specific container.

```

class Array;
class Iterator {
public:
    Iterator(Array &array);
    void reset();
    int *next();
private:
    int m_iterator;
    Array &m_array;
};

```

```

class Array {
    friend int *Iterator::next(Array &array);
public:
    Array(int arraySize);
    ~Array();
    void insertElement(int slot, int element);
private:
    int m_arraySize;
    int *m_array;
};

```

16

Iterators (Cont'd)

```

int *Iterator::next() {
    m_iterator++;
    if (m_iterator < m_array.m_arraySize)
        return &m_array.m_array[m_iterator];
    return 0;
}

void main() {
    int result = 0;
    Array array(2);
    Iterator iter1(array), iter2(array);
    int *i, *j;

    array.insertElement(0, 2);
    array.insertElement(1, 3);
    for(i= iter1.next(); i!=0; i=iter1.next(), iter2.reset())
        for(j=iter2.next(); j!=0; j=iter2.next())
            result += pow(j, i);
    cout << "Result = " << result << endl;
}

```

$2^2 + 3^2 + 2^3 + 3^3$

Iterator::Iterator(Array &array)
 \vdots m_iterator(-1),
 \vdots m_array(array) {

void Iterator::reset() {
 \vdots m_iterator = -1;
}

Output
Result = 48

17

Inner Class Implementation (cont'd)

```

int *Array::Iterator::next(Array &array) {
    m_iterator++;
    if (m_iterator < array.m_arraySize)
        return &array.m_array[m_iterator];
    return 0;
}

void main() {
    int result = 0;
    Array array(2);
    Array::Iterator iter1, iter2;
    int *i, *j;

    array.insertElement(0, 2);
    array.insertElement(1, 3);
    for(i= iter1.next(array); i!=0; i=iter1.next(array), iter2.reset())
        for(j=iter2.next(array); j!=0; j=iter2.next(array))
            result += pow(j, i);
    cout << "Result = " << result << endl;
}

```

$2^2 + 3^2 + 2^3 + 3^3$

Array::Iterator::Iterator(): m_iterator(-1) {
}

void Array::Iterator::reset() {
 \vdots m_iterator = -1;
}

Output
Result = 48

19

Inner Class Implementation

```

class Array
{
    friend int *Iterator::next(Array &array);
public: <---- do not need to specify Array::
    class Iterator
    {
    public:
        Iterator();
        void reset();
        int *next(Array &array);
    private:
        int m_iterator;
    };
    Array(int arraySize);
    ~Array();
    void insertElement(int slot, int element);
private:
    int m_arraySize;
    int *m_array;
};

```

public/private specifies whether codes outside Array can use Iterator class definition or not.

Note: An inner class is basically an independent class from its host class, it is not allowed to access the private parts of the host class.

18

Friends and Inheritance

- Friends of **Base** class are not automatically friends of **Derived** class (i.e. friendship relationship is not inheritable)

```

class Base {
    friend class Friend;
private:
    int m_baseData;
};

class Derived: public Base {
// friend class Friend;
private:
    int m_derivedData;
};

class Friend {
public:
    void func1(Base &base);
    void func2(Derived &derived);
};

void Friend::func1(Base &base) {
    cout << base.m_baseData << endl;
}

void Friend::func2(Derived &derived) {
    cout << derived.m_derivedData << endl;
}

```

error C2248: 'm_derivedData' : cannot access private member declared in class 'Derived'

20